

UNCLASSIFIED

AD NUMBER

ADA801445

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to DoD only;
Administrative/Operational Use; 03 NOV 1948.
Other requests shall be referred to National
Aeronautics and Space Administration,
Washington, DC. Pre-dates formal DoD
distribution statements. Treat as DoD only.

AUTHORITY

NASA TR Server website

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

Copy No.

6

RM No. L8D14

3 1176 00003 3648

4 NOV 1948



RESEARCH MEMORANDUM

PRELIMINARY CORRELATION OF THE EFFECT OF COMPRESSIBILITY ON
THE LOCATION OF THE SECTION AERODYNAMIC
CENTER AT SUBCRITICAL SPEEDS

By

Edward C. Polhamus

Langley Aeronautical Laboratory
Langley Field, Va.

CLASSIFIED DOCUMENT

This document contains classified information affecting the National Defense of the United States within the meaning of the Espionage Act, USC 50:31 and 32. Its transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law. Information so classified may be imparted only to persons in the military and naval services of the United States, appropriate civilian officers and employees of the Federal Government who have a legitimate interest therein, and to United States citizens of known loyalty and discretion who of necessity must be informed thereof.

CLASSIFICATION CANCELLED

Authority J. W. Crowley
Date 12/14/53
By 2028A 2/19/54
R. F. 1989
See NACA

NATIONAL ADVISORY COMMITTEE
FOR AERONAUTICS

WASHINGTON
November 3, 1948

NACA LIBRARY
LANGLEY MEMORIAL AERONAUTICAL
LABORATORY
Langley Field, Va.

~~RESTRICTED~~

UNCLASSIFIED

NACA RM No. L8D14

UNCLASSIFIED

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

RESEARCH MEMORANDUM

PRELIMINARY CORRELATION OF THE EFFECT OF COMPRESSIBILITY ON
THE LOCATION OF THE SECTION AERODYNAMIC
CENTER AT SUBCRITICAL SPEEDS

By Edward C. Polhamus

SUMMARY

A correlation of available two-dimensional airfoil data to determine the effects of compressibility on the location of the section aerodynamic center at low lift coefficients has been made. The results indicate that large forward or rearward movements of the aerodynamic center with Mach number are possible. It appears that thickness ratio is an important parameter controlling the variation with Mach number. For the 6-percent-thick airfoils the aerodynamic center moved rearward with increasing Mach number, while for the thicker airfoils (9 and 12 percent) the movement was forward. It appears that airfoils of 7- or 8-percent thickness ratios might experience the least variation of the aerodynamic center with Mach number.

SYMBOLS

M Mach number
a.c. aerodynamic center
t airfoil maximum thickness
c airfoil chord
 ϕ trailing-edge angle (included angle between upper and lower
 surfaces at last 5 percent of chord), degrees

INTRODUCTION

A theoretical study (reference 1) has indicated that the rate of increase with Mach number for both the lift coefficient and the pitching-moment coefficient of a two-dimensional airfoil is very nearly the same at subcritical Mach numbers, and that, therefore, little shift in the

UNCLASSIFIED

aerodynamic center is to be expected. Experimental investigations (for example, reference 2), however, have indicated that shifts in the section-aerodynamic-center position as large as 0.05 chord have occurred within the subcritical Mach number range and that such shifts may be either forward or rearward. The present paper presents the results of a preliminary analysis of available data on the pitching-moment characteristics of airfoils at Mach numbers between 0.4 and the lift break, to determine what parameters control the variation of the section-aerodynamic-center position with Mach number.

BASIS OF ANALYSIS

The data used in the correlation were obtained from references 2 to 6, and a list of the airfoils used is presented in table I. The location of the aerodynamic center was determined from the slope of the pitching-moment curve in the low lift-coefficient range which, in some cases because of reversals, was limited to ± 0.1 . This correlation, therefore, is primarily concerned with the aerodynamic-center travel with Mach number near zero lift. All the data were obtained at Reynolds numbers less than 2×10^6 with free transition. Although the data for some of the airfoils examined extend to Mach numbers beyond the break in the lift force, the correlation is primarily limited to Mach numbers up to the lift break. The correlation begins at a Mach number of 0.4 due to the fact that the investigations from which the correlation was made began at a Mach number of 0.4. The results were obtained from tests of airfoils with thickness ratios of 6, 9, and 12 percent.

DISCUSSION

The results of the correlation of the various airfoils listed in table I are presented in figure 1. The various crosshatched regions in figure 1 define the measured limits of the shift in the aerodynamic-center location of the various airfoils relative to its position at a Mach number of 0.4 for various airfoil thickness ratios. The thickness ratio was selected because, from the data, it appeared to be the most influential parameter controlling the variation of the aerodynamic-center location with Mach number. The results indicate that for 6-percent airfoils the section aerodynamic center moves rearward with increasing Mach number with shifts as large as 12 percent of the chord being attained. For the thicker airfoils (9 and 12 percent) however, the section aerodynamic center moves forward with increasing Mach number.

It appears from interpolation of the data that airfoils with thickness ratios of 7 or 8 percent might be expected to experience the least variation of the aerodynamic-center position with Mach number.

A low-speed study of the effect of trailing-edge modifications on the pitching-moment characteristics of airfoils (reference 7) indicated that the trailing-edge angle had a large effect on the location of the aerodynamic center. In figure 1 the range of trailing-edge angles for each thickness ratio is presented, but there appeared to be no systematic variation with trailing-edge angle for a given thickness ratio. However, in the present correlation, changes in trailing-edge angles were always accompanied by other changes in the airfoil shape, while in reference 7 changes in trailing-edge angle were obtained by modifying the trailing edge of a given airfoil by means of bevels and cusps. Inasmuch as the effects of the various modifications which accompanied changes in trailing-edge angle could not be separated, no further refinements in the correlation appear to be possible at the present time.

It will be noted that none of the airfoils used in the correlation are of the low-drag type. Available low-drag data (reference 8) indicate that although large shifts in the aerodynamic-center position with Mach number are possible they do not consistently fall within the bands of figure 1. Until more low-drag data are available no definite conclusions with regard to low-drag sections can be made.

It should be kept in mind that section characteristics alone are not sufficient for predicting the characteristics of finite-span wings. The chordwise shift in the center of the induced load caused by the variation of the effective aspect ratio with Mach number and the chordwise shift due to the spanwise shift of the center of pressure with Mach number on swept wings may be appreciable.

CONCLUSIONS

Based on a preliminary correlation of the effect of compressibility on the location of the section aerodynamic center near zero lift, the following conclusions were reached:

1. Forward or rearward movements of the aerodynamic center as large as 12 percent of the chord were observed.
2. For 6-percent-thick airfoils the aerodynamic center moved rearward with increasing Mach number, while for the thicker airfoils (9 and 12 percent) the aerodynamic center moved forward with increasing Mach number.

3. It appeared that airfoils having thickness ratios of 7 or 8 percent might experience the least variations of the aerodynamic center with Mach number.

Langley Aeronautical Laboratory
National Advisory Committee for Aeronautics
Langley Field, Va.

REFERENCES

1. Kaplan, Carl: A Theoretical Study of the Moment on a Body in a Compressible Fluid. NACA Rep. No. 671, 1939.
2. Ferri, Antonio: Completed Tabulation in the United States of Tests of 24 Airfoils at High Mach Numbers (Derived from Interrupted Work at Guidonia, Italy, in the 1.31- by 1.74-Foot High-Speed Tunnel). NACA ACR L5E21, 1945.
3. Stack, John, and Von Doenhoff, Albert E.: Tests of 16 Related Airfoils at High Speeds. NACA Rep. No. 492, 1934.
4. Stevenson, David B., and Byrne, Robert W.: High-Speed Wind-Tunnel Tests of an NACA 16-009 Airfoil Having a 32.9-Percent-Chord Flap with an Overhang 20.7 Percent of the Flap Chord. NACA TN No. 1406, 1947.
5. Stevenson, David B., and Adler, Alfred A.: High-Speed Wind-Tunnel Tests of an NACA 0009-64 Airfoil Having a 33.4-Percent-Chord Flap with an Overhang 20.1 Percent of the Flap Chord. NACA TN No. 1417, 1947.
6. Lindsey, W. F., Stevenson, D. B., and Daley, Bernard N.: Aerodynamic Characteristics of 24 NACA 16-Series Airfoils at Mach Numbers between 0.3 and 0.8. NACA TN No. 1546, 1948.
7. Purser, Paul E., and Johnson, Harold S.: Effects of Trailing-Edge Modifications on Pitching-Moment Characteristics of Airfoils. NACA CB No. L4I30, 1944.
8. Van Dyke, Milton D., and Wibbert, Gordon A.: High-Speed Aerodynamic Characteristics of 12 Thin NACA 6-Series Airfoils. NACA MR No. A5F27, Army Air Forces, 1945.

TABLE I
AIRFOILS USED IN CORRELATION

Airfoil	Reference
NACA 0006-34	2
NACA 0006-63	2,3
NACA 0006-64	2
NACA 0006T	2
NACA 2306	2
NACA 2406	2
NACA M1 (6 percent)	2
NACA 16-306	6
NACA 16-506	6
NACA 16-009	4
NACA 0009-62	2,3
NACA 0009-63	2,3
NACA 0009-64	2,3,5
NACA 0009-93	3
NACA 0009-33	3
NACA 0009-03	3
NACA 2309	2
NACA 2409	2
NACA 2509	2
NACA 16-109	6
NACA 16-309	6
NACA 16-509	6
Davis (9 percent)	2
ETH 3609	2
NACA 0012-63	3
NACA 0012-64	2
NACA 0012-34	2
NACA 2312	2
NACA 2412	2
NACA 16-212	Unpublished
NACA 16-312	6
NACA 16-512	6






Figure 1.-Effect of Mach number on the location of the section aerodynamic center at low lift coefficients.

TITLE: Preliminary Correlation of the Effect of Compressibility on the Location of the Section Aerodynamic Center at Subcritical Speeds

AUTHOR(S): Polhamus, Edward C.

ORIGINATING AGENCY: Langley Aeronautical Lab., Langley Field, Va.

PUBLISHED BY: National Advisory Committee for Aeronautics, Washington, D. C.

ATI- 40723

REVISION

(None)

ORIG. AGENCY NO.

RM-L8D14

PUBLISHING AGENCY NO.

(Same)

DATE	DOC. CLASS.	COUNTRY	LANGUAGE	PAGES	ILLUSTRATIONS
Nov '48	SECRET	U.S.	Eng.	7	table, graph

ABSTRACT:

A correlation of available two-dimensional airfoil data has been made to determine the effects of compressibility on the location of the section aerodynamic center at low lift coefficients. The results indicate that large forward or rearward movements of the aerodynamic center with Mach number are possible. It appears that thickness ratio is an important parameter controlling the variation with Mach number. For 6% thick airfoils, the aerodynamic center moved rearward with increasing Mach number; while for the thicker airfoils of 9 to 12%, the movement was forward. It appears that airfoils of 7 or 8% thickness ratios might experience the least variation of the aerodynamic center with Mach number.

DISTRIBUTION: Request copies of this report only from Publishing Agency

DIVISION: Aerodynamics (2)
SECTION: Wings and Airfoils (6)

SUBJECT HEADINGS: Airfoils - Compressibility effects (08032); Wings - Mach number effect (99171.2)

ATI SHEET NO.: R-2-6-110

Air Documents Division, Intelligence Department
Air Materiel Command

AIR TECHNICAL INDEX

Wright-Patterson Air Force Base
Dayton, Ohio

Uauth: naca Research abstracts no
56dd 13 Jan. 54